



REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	PR2298	05-JAN-12	GMx

ÜBERARBEITET
08:51, 03.03.2014



220V-240V WIRING

7. COMPONENTS MARKED WITH THIS SYMBOL:
SHALL BE REPLACED WITH EXACT SAME TYPE AS SPECIFIED
BY FMIC IF SERVICE IS NECESSARY (SAFETY REQUIREMENT).
BY AC AND DC VOLTMETERS REFERENCED TO GROUND WITH
A DVM UNDER THE FOLLOWING CONDITIONS:

UNIT AT RATED LINE VOLTAGE
8 OHM RESISTIVE LOAD CONNECTED AT SPEAKER JACK (J8)
NO AC INPUT (J4, J5 & J6) FOR DC TESTS

ADDITIONAL NOTES FOR AC TESTS (TP = OVAL):

AC INPUT TO GUITAR INPUT (J4-J6) = 10mV AT 1kHz.

VOLUME CONTROL SET TO MAX CW ROTATION.

TREMOLO CONTROL SET TO OFF (FULLY CCW) POSITION

- EXCEPT FOR AC MEASUREMENTS ON TP16 & TP17.

ROTATE VOLUME & TREMOLO CONTROLS CCW WITH AC INPUT

TO CONFIRM R13 & R53 OK. MONITOR TP15 OR

INTERNAL SPEAKER FOR REDUCED OUTPUT.

5. ALL TUBES INSTALLED IN CHASSIS MOUNTED SOCKETS.

4. THIS SCHEMATIC IS FOR PCB FABRICATION P/N 2298CAX021 AND

PCB ASSEMBLY P/N 2298CAX022.

3. ALL POLARIZED CAPACITORS IN μ F, 10X OR BETTER; 50V MINIMUM.

2. ALL UNPOLARIZED CAPACITORS IN μ F, 20%; 50V MINIMUM.
(POWER SUPPLY BYPASS CAPACITORS ARE 20%).

1. ALL RESISTORS IN OHMS, 5%, 1/4W, UNLESS NOTED.

NOTES: (UNLESS OTHERWISE NOTED)

THIS DOCUMENT CONTAINS INFORMATION OF
A PROPRIETARY NATURE TO FENDER MUSICAL
INSTRUMENTS AND IS SUBMITTED TO YOU IN
CONFIDENCE AND SHALL NOT BE DISCLOSED OR
TRANSMITTED TO OTHERS WITHOUT AUTHORIZ-
ATION FROM FENDER MUSICAL INSTRUMENTS.

CHECKED BY: _____

DATE: _____

APPROVED BY: _____

DATE: _____

DRAWN: G McMillen ENGR: S MARSHALL

DATABASE FILE: Z2298S.SCH

MUSICAL INSTRUMENTS
Corona, CA U.S.A.

TITLE: SERVICE DIAGRAM, COMBINED (schematic)

PAWNSHOP EXCELSIOR

SIZE DRAWING NUMBER REV.

D 2298CAX020 A

RELEASE DATE: 05-JAN-12 SHEET: 1 OF 2

8 7 6 5 4 3 2 1

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	PR2298	05-JAN-12	GMx

